



<https://wearwell.com/>

LockSafe Heavy Duty Drainage, NBR Rubber with GRITSHIELD

Group 589

LockSafe Heavy Duty with GRITSHIELD takes slip resistance to the extreme and is the perfect combination of safety, durability, and comfort. The addition of GRITSHIELD provides more traction with a better coefficient of friction.

GRITSHIELD empowers workers to walk with confidence and move in any environment where slips and falls were previously a constant threat. The surface of the tile features a unique raised cylinder design intermixed with a uniform series of drainage holes- combining excellent slip resistance with industry-leading airflow, drainage, and material pass-through.

The LockSafe Heavy Duty with GRITSHIELD mat is so robust it can even be placed directly over open grating. The patented LockSafe positive interlock system keeps tiles together and is easy to customize on-site to fit your space.

Choose the LockSafe Heavy Duty with GRITSHIELD for unmatched durability, safety, and performance in the slickest areas.

This 3/4 In. (19 mm) thick, 3x3 Ft. (.91x.91 m) interlocking modular tile is built to withstand the harshest and most relentless work conditions.

- Cut lengths are not available for this product
- Full customization available
- Available in 3x3 Ft. (.91x.91 m) interlocking modular tiles. Allows for full do it yourself customization on-site
- Proudly manufactured in North America in Guadalajara, Mexico
- Patent Pending

Wearwell Categories

Suitable Environment	Dry Floors, Oily
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Material	Nitrile Rubber (NBR)
Recycled	20%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.1 / Wet COF = .96
Compression Deflection	ASTM D575 - 16.4psi @ 25% = .24" distance compressed
Tear Strength	Not Applicable
ESD Rating	Not Rated for ESD Applications
Dielectric Strength	Not Rated for Switchboard Applications

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
589.34x3x3NBRBK		Black	3/4 In. (19 mm)		Y	EA