



www.wearwell.com

24/Seven® LockSafe® Solid NBR

Group 577-NBR

You invest a lot of time and money in your matting program. There is a ton of effort that goes into making the right decision, getting the approvals, scheduling the install and getting those mats in place. Choose 24/SEVEN® LockSafe® with a patent pending Positive Interlock System, so you can “lockdown” the mats securely and they stay together. Positive systems lock in: Both male and female connectors have a flange that lock together and provide a secure connection in all directions. Why it matters: They don’t come apart until you want them to! Lift up, roll up and roll away for removal or maintenance.

Available in 2 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- NBR- Petroleum-based fluids
- Hidden positive interlocking system
- Choice of solid, domed or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12" (30 cm) increments
- Overall thickness 5/8" (16 mm)

Type	Anti-Fatigue Matting
Suitable Environment	Wet, Oily
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	Nitrile Rubber
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'B'; Rating
Taber Abrasion	ASTM D3884 / Modified 2%
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .54 / Wet COF = .45
Compression Deflection	16.5 @ 25%
Tear Strength	Not Available
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
577.58x3x3NBRBK		Black	0.625	3' x 3'	Y	EA