



[www.wearwell.com](http://www.wearwell.com)

## 24/Seven® LockSafe® Solid NBR w/Gritshield Group 584-NBR

You invest a lot of time and money in your matting program. There is a ton of effort that goes into making the right decision, getting the approvals, scheduling the install and getting those mats in place. Choose 24/SEVEN LockSafe with a patent pending Positive Interlock System, so you can “lockdown” the mats securely and they stay together. Positive systems lock in: Both male and female connectors have a flange that lock together and provide a secure connection in all directions. Why it matters: They don’t come apart until you want them to! Lift up, roll up and roll away for removal or maintenance.

- NBR- Petroleum-based fluids
- Hidden positive interlocking system
- Choice of solid, domed or drainage styles
- Choose GRITSHIELD for increased traction
- Create your own custom widths or lengths in 12” (30 cm) increments
- Overall thickness 5/8" (16 mm)

<b>Type</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Wet, Oily
<b>Customization Level</b>	C3 - Full Custom (Length, Width, Shape)
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	Nitrile Rubber
<b>Recycled</b>	>50%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = 020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
584.58x3x3NBRBK	715411702916	Black	0.625	3' x 3'	Y	EA