

## 24/Seven LockSafe Female Edging, Grease Resistant Black



### Group 578-FGRBK

24/Seven LockSafe female edging is Grease Resistant and securely interlocks with 24/Seven LockSafe modular tiles. Black edging creates a seamless and smooth transition for foot traffic.

Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

- Grease Resistant Natural Rubber (GR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and Male Edging available
- Also available in yellow

[www.wearwell.com](http://www.wearwell.com)

<b>Art</b>	Anti-Fatigue Flooring
<b>Geeignete Umwelt</b>	Trocken, feucht, Rutschig
<b>Anpassung Ebene</b>	C3 - Full Custom (Length, Width, Shape)
<b>Feste oder Drainage</b>	Solid
<b>zusammengesetzt</b>	Grease Resistant Natural Rubber (GR)
<b>Recycelt</b>	>50%
<b>Garantie</b>	

Property	Test / Result
Entzündbarkeit	MVSS 302 / 'A'; Rating
Taber Abnutzung	Federal Standard 191 Modified / 1% loss
Temperaturspanne	10 to 140 F
Coefficient der Friktion	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Kompression Ablenkung	Not Available
der Riss Schwere	Not Available
ESD Bewertung	Not Available
Dielektrische Festigkeit	Not Available

Teilenummer	UPC	Farbe	Dicke	Maße	Auf lagerteil	UOM
-------------	-----	-------	-------	------	---------------	-----