



www.wearwell.com

24/Seven GR (Grease Resistant) Female Edging - Black

Group 572-FGRBK

24/Seven GR (Grease Resistant) female edging securely interlocks with 24/Seven GR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

Art Anti-Fatigue Flooring

Geeignete Umwelt Trocken, feucht, Rutschig

Anpassung Ebene C3 - Full Custom (Length, Width, Shape)

Feste oder Drainage Solid

zusammengesetzt Grease Resistant Natural Rubber (GR)

Recycelt >50%

Garantie 1 Year

Property	Test / Result
Entzündbarkeit	MVSS 302 / 'A'; Rating
Taber Abnutzung	Federal Standard 191 Modified / 1% loss
Temperaturspanne	10 to 140 F
Coefficient der Friktion	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
Kompression Ablenkung	Not Available
der Riss Schwere	Not Available
ESD Bewertung	Not Available
Dielektrische Festigkeit	Not Available

Teilenummer	UPC	Farbe	Dicke	Maße	Auf lagerteil	UOM
-------------	-----	-------	-------	------	---------------	-----