



www.wearwell.com

24/Seven LockSafe GR Ecke, schwarz

Group 578-CGRBK

24/Seven LockSafe corners offer a secure connection with ramps and tiles. These separate corners alleviate the time, costs, and waste associated with traditional modular rubber edging that requires cutting.

Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

- For use in dry areas or areas with water
- Grease Resistant Natural Rubber (GR)
- Case of 4
- 3" wide
- Overall thickness 5/8"
- Male and female edging available
- Available in black and yellow

Art Anti-Fatigue Flooring

Geeignete Umwelt Trocken, feucht, Rutschig

Anpassung Ebene C3 - Full Custom (Length, Width, Shape)

Feste oder Drainage Solid

zusammengesetzt Grease Resistant Natural Rubber (GR)

Recycelt >50%

Garantie 1 Year

Property	Test / Result
Entzündbarkeit	MVSS 302 / 'A'; Rating
Taber Abnutzung	Federal Standard 191 Modified / 1% loss
Temperaturspanne	10 to 140 F
Coefficient der Friktion	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Kompression Ablenkung	Not Available
der Riss Schwere	Not Available
ESD Bewertung	Not Available
Dielektrische Festigkeit	Not Available

Teilenummer	UPC	Farbe	Dicke	Maße	Auf lagerteil	UOM
-------------	-----	-------	-------	------	---------------	-----