

24/Seven LockSafe NBR Männliche Randleiste, schwarz

Group 578-MNBRBK

24/Seven LockSafe Nitrile Rubber (NBR) male edging securely interlocks with 24/Seven LockSafe NBR modular tiles. NBR is suitable for more demanding areas that require optimum chemical resistance. Black edging creates a seamless and smooth transition for foot traffic.

- Nitrile Rubber (NBR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and female edging available
- Available in black and yellow

www.wearwell.com

Art	Anti-Fatigue Flooring
Geeignete Umwelt	Trocken, feucht, ölig, Rutschig
Anpassung Ebene	C3 - Full Custom (Length, Width, Shape)
Feste oder Drainage	Solid
zusammengesetzt	Nitrile Rubber (NBR)
Recycelt	>50%
Garantie	1 Year

Property	Test / Result
Entzündbarkeit	MVSS 302 / 'A'; Rating
Taber Abnutzung	Federal Standard 191 Modified / 1% loss
Temperaturspanne	10 to 140 F
Coefficient der Friktion	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Kompression Ablenkung	Not Applicable
der Riss Schwere	Not Applicable
ESD Bewertung	Not Applicable
Dielektrische Festigkeit	Not Applicable

Teilenummer	UPC	Farbe	Dicke	Maße	Auf lagerteil	UOM
-------------	-----	-------	-------	------	---------------	-----