

24/Seven® LockSafe® MAX Female Edging, 8 cm x 91 cm - Yellow

Group 581.FGRYL



www.wearwell.com

[24/SEVEN® LockSafe® MAX](#) female edging is grease-resistant and securely interlocks with 24/SEVEN® LockSafe® MAX modular tiles. Yellow edging acts as a visual cue and smooth transition for foot traffic. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

For use with 24/Seven Locksafe MAX series products only.

- For dry areas or areas with water
- Grease Resistant (Natural Rubber)
- 4 in. x 36 in. (8 cm x 91 cm) Overall thickness 1 inch (25 mm)
- Also available in [black](#)
- [Corners](#) and [male](#) edging available
- U.S. PATENT No. D882,293 S

Art	Anti-Fatigue Flooring
Geeignete Umwelt	Trocken
Anpassung Ebene	C3
Feste oder Drainage	Solid
zusammengesetzt	GR/Natural Rubber
Recycelt	25%
Garantie	1 Year

Property	Test / Result
Entzündbarkeit	MVSS 302 / 'A'; Rating
Taber Abnutzung	Federal Standard 191 Modified / 1% loss
Temperaturspanne	10 to 140 F
Coefficient der Friktion	ASTM F1677 / Dry: .90 / Wet .020
Kompression Ablenkung	Not Available
der Riss Schwere	Not Available
ESD Bewertung	Not Available
Dielektrische Festigkeit	Not Available

Teilenummer	UPC	Farbe	Dicke	Maße	Auf lagerteil	UOM
-------------	-----	-------	-------	------	---------------	-----