

24/Seven® LockSafe® MAX Male Edging, 8 cm x 91 cm - Yellow

Group 581.MGRYL



www.wearwell.com

[24/SEVEN® LockSafe® MAX](#) male edging is Grease Resistant and securely interlocks with 24/SEVEN® LockSafe® MAX modular tiles. Yellow edging acts as a visual cue and smooth transition for foot traffic. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or wet areas where the primary liquid is water.

For use with 24/Seven Locksafe MAX series products only.

- For dry areas or areas with water
- Grease-resistant (Natural Rubber)
- 4 in. x 36 in. (8 cm x 91 cm)
- Overall thickness 1 in (25 mm)
- Also available in [black](#)
- [Corners](#) and [female](#) edging available
- U.S. PATENT No. D882,293 S

| | |
|----------------------------|-----------------------|
| Art | Anti-Fatigue Flooring |
| Geeignete Umwelt | Trocken |
| Anpassung Ebene | C3 |
| Feste oder Drainage | Solid |
| zusammengesetzt | GR/Natural Rubber |
| Recycelt | 25% |
| Garantie | 1 Year |

| Property | Test / Result |
|--------------------------|---|
| Entzündbarkeit | MVSS 302 / 'A'; Rating |
| Taber Abnutzung | Federal Standard 191 Modified / 1% loss |
| Temperaturspanne | 10 to 140 F |
| Coefficient der Friktion | ASTM F1677 / Dry: .90 / Wet .020 |
| Kompression Ablenkung | Not Available |
| der Riss Schwere | Not Available |
| ESD Bewertung | Not Available |
| Dielektrische Festigkeit | Not Available |

| | | | | | | |
|-------------|-----|-------|-------|------|---------------|-----|
| Teilenummer | UPC | Farbe | Dicke | Maße | Auf lagerteil | UOM |
|-------------|-----|-------|-------|------|---------------|-----|