


www.wearwell.com

Tapete Diel Ectrico Corrugado De Doble Funci On - Negro

Group 720BK

Switchboard matting protects workers from harmful, even deadly shock. This unique non-conductive anti-fatigue mat features a premium Nitricell sponge base, making it first in class for comfort and safety.

- "Best" sponge base

NSFI Certified

- Surface conforms to ANSI/ASTM D178 01, Type II, Class 2
- Insulates up to 40,000 volts of electricity
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness 5/8"

Tipo Non-Conductive Anti-Fatigue Matting

Medio Ambiente adecuado Seco

Nivel de personalización C1 - Custom Length

Drenaje o Sólidos Solid

Compuesto PVC Surface With Nitrile Infused Sponge

Reciclado <10%

Garantía 1 Year

| Property | Test / Result |
|-------------------------|--|
| Inflamabilidad | ASTM D178-01: 0.224 mm /s |
| abrasión Taber | Fed. Std. 191: 1% lost @ 1,000 cycles |
| Rango de temperatura | Not Available |
| Coeficiente de Fricción | ASTM F1677: Dry COF .91 |
| compresión de Deflexión | Not Available |
| resistencia al desgarro | ASTM D412-98a Die C 1212 psi |
| Valoración esd | Not Applicable |
| resistencia dieléctrica | Surface conforms to ANSI/ASTM D178 01, Type II, Class 2: 30,000 volts. (Recommended Max Usage up to 17,000 volts) |

| Número de parte | UPC | Color | Grosor | Dimensiones | Parte común | UOM |
|-----------------|--------------|-------|--------|-------------|-------------|-----|
| 720.58x3X5BK | 715411003167 | Black | 0.625 | 3' x 5' | Y | EA |
| 720.58x3X75BK | 715411003860 | Black | 0.625 | 3' x 75' | Y | RL |