



www.wearwell.com

## Tapete Diel Ectrico Corrugado De Doble Funci On - Negro con bordes amarillos

### Group 720BYL

Switchboard matting protects workers from harmful, even deadly shock. This unique non-conductive anti-fatigue mat features a premium Nitricell sponge base, making it first in class for comfort and safety.

- "Best" sponge base

#### NSFI Certified

- Surface conforms to ANSI/ASTM D178 01, Type II, Class 2
- Insulates up to 40,000 volts of electricity
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness 5/8"

**Tipo** Non-Conductive Anti-Fatigue Matting

**Medio Ambiente adecuado** Seco

**Nivel de personalización** C1 - Custom Length

**Drenaje o Sólidos** Solid

**Compuesto** PVC Surface With Nitrile Infused Sponge

**Reciclado** <10%

**Garantía** 1 Year

Property	Test / Result
Inflamabilidad	ASTM D178-01: 0.224 mm /s
abrasión Taber	Fed. Std. 191: 1% lost @ 1,000 cycles
Rango de temperatura	Not Available
Coeficiente de Fricción	ASTM F1677: Dry COF .91
compresión de Deflexión	Not Available
resistencia al desgarro	ASTM D412-98a Die C 1212 psi
Valoración esd	Not Applicable
resistencia dieléctrica	Surface conforms to ANSI/ASTM D178 01, Type II, Class 2: 30,000 volts. (Recommended Max Usage up to 17,000 volts)

Número de parte	UPC	Color	Grosor	Dimensiones	Parte común	UOM
720.58x3X5BYL	715411003464	Black w/Yellow Borders	0.625	3' x 5'	Y	EA
720.58x3X75BYL	715411003341	Black w/Yellow Borders	0.625	3' x 75'	Y	RL