


www.wearwell.com

24/Seven GR (Grease Resistant) Male Edging - Black

Group 572-MGRBK

24/Seven GR (Grease Resistant) male edging securely interlocks with 24/Seven GR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

Tipo	Anti-Fatigue Flooring
Medio Ambiente adecuado	Seco, Húmedo, Resbaladizo
Nivel de personalización	C3 - Full Custom (Length, Width, Shape)
Drenaje o Sólidos	Solid
Compuesto	Grease Resistant Natural Rubber (GR)
Reciclado	>50%
Garantía	1 Year

Property	Test / Result
Inflamabilidad	MVSS 302 / 'A'; Rating
abrasión Taber	Federal Standard 191 Modified / 1% loss
Rango de temperatura	10 to 140 F
Coeficiente de Fricción	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
compresión de Deflexión	Not Available
resistencia al desgarro	Not Available
Valoración esd	Not Available
resistencia dieléctrica	Not Available

Número de parte	UPC	Color	Grosor	Dimensiones	Parte común	UOM
-----------------	-----	-------	--------	-------------	-------------	-----