



www.wearwell.com

## 24/Seven GR (Grease Resistant) Male Edging - Yellow

### Group 572-MGRYL

24/Seven GR (Grease Resistant) male edging securely interlocks with 24/Seven GR rubber floor tiles. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

<b>Tipo</b>	Anti-Fatigue Flooring
<b>Medio Ambiente adecuado</b>	Seco, Húmedo, Resbaladizo
<b>Nivel de personalización</b>	C3 - Full Custom (Length, Width, Shape)
<b>Drenaje o Sólidos</b>	Solid
<b>Compuesto</b>	Grease Resistant Natural Rubber (GR)
<b>Reciclado</b>	>50%
<b>Garantía</b>	1 Year

Property	Test / Result
Inflamabilidad	MVSS 302 / 'A'; Rating
abrasión Taber	Federal Standard 191 Modified / 1% loss
Rango de temperatura	10 to 140 F
Coeficiente de Fricción	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
compresión de Deflexión	Not Available
resistencia al desgarro	Not Available
Valoración esd	Not Available
resistencia dieléctrica	Not Available

Número de parte	UPC	Color	Grosor	Dimensiones	Parte común	UOM
-----------------	-----	-------	--------	-------------	-------------	-----