



www.wearwell.com

24/Seven CFR Rampa Hembra, Color Negro

Group 572-FCFRBK

24/Seven CFR (Cutting Fluid Resistant) female edging securely interlocks with 24/Seven CFR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

Tipo Anti-Fatigue Flooring

Medio Ambiente adecuado Seco, Húmedo, Aceitoso, Resbaladizo

Nivel de personalización C3 - Full Custom (Length, Width, Shape)

Drenaje o Sólidos Solid

Compuesto Cutting Fluid Resistant Rubber (CFR)

Reciclado >50%

Garantía 1 Year

| Property | Test / Result |
|-------------------------|--|
| Inflamabilidad | MVSS 302 / 'A'; Rating |
| abrasión Taber | Federal Standard 191 Modified / 1% loss |
| Rango de temperatura | 10 to 140 F |
| Coeficiente de Fricción | ASTM F1677 / Dry: COF = .90 / Wet COF = .020 |
| compresión de Deflexión | Not Available |
| resistencia al desgarro | Not Available |
| Valoración esd | Not Available |
| resistencia dieléctrica | Not Available |

| | | | | | | |
|-----------------|-----|-------|--------|-------------|-------------|-----|
| Número de parte | UPC | Color | Grosor | Dimensiones | Parte común | UOM |
|-----------------|-----|-------|--------|-------------|-------------|-----|