



www.wearwell.com

24/Seven CFR Rampa Hembra, Color Amarillo

Group 572-FCFRYL

24/Seven CFR (Cutting Fluid Resistant) female edging securely interlocks with 24/Seven CFR rubber floor tiles. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Male edging available
- Available in black and yellow

Tipo Anti-Fatigue Flooring

Medio Ambiente adecuado Seco, Húmedo, Aceitoso, Resbaladizo

Nivel de personalización C3 - Full Custom (Length, Width, Shape)

Drenaje o Sólidos Solid

Compuesto Cutting Fluid Resistant Rubber (CFR)

Reciclado >50%

Garantía 1 Year

Property	Test / Result
Inflamabilidad	MVSS 302 / 'A'; Rating
abrasión Taber	Federal Standard 191 Modified / 1% loss
Rango de temperatura	10 to 140 F
Coeficiente de Fricción	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
compresión de Deflexión	Not Available
resistencia al desgarro	Not Available
Valoración esd	Not Available
resistencia dieléctrica	Not Available

Número de parte	UPC	Color	Grosor	Dimensiones	Parte común	UOM
-----------------	-----	-------	--------	-------------	-------------	-----