

## 24/Seven® LockSafe® MAX Female Edging, 8 cm x 91 cm - Yellow

Group 581.FGRYL



www.wearwell.com

[24/SEVEN® LockSafe® MAX](#) female edging is grease-resistant and securely interlocks with 24/SEVEN® LockSafe® MAX modular tiles. Yellow edging acts as a visual cue and smooth transition for foot traffic. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

**For use with 24/Seven Locksafe MAX series products only.**

- For dry areas or areas with water
- Grease Resistant (Natural Rubber)
- 4 in. x 36 in. (8 cm x 91 cm) Overall thickness 1 inch (25 mm)
- Also available in [black](#)
- [Corners](#) and [male](#) edging available
- U.S. PATENT No. D882,293 S

<b>Tipo</b>	Anti-Fatigue Flooring
<b>Medio Ambiente adecuado</b>	Seco
<b>Nivel de personalización</b>	C3
<b>Drenaje o Sólidos</b>	Solid
<b>Compuesto</b>	GR/Natural Rubber
<b>Reciclado</b>	25%
<b>Garantía</b>	1 Year

Property	Test / Result
Inflamabilidad	MVSS 302 / 'A'; Rating
abrasión Taber	Federal Standard 191 Modified / 1% loss
Rango de temperatura	10 to 140 F
Coeficiente de Fricción	ASTM F1677 / Dry: .90 / Wet .020
compresión de Deflexión	Not Available
resistencia al desgarro	Not Available
Valoración esd	Not Available
resistencia dieléctrica	Not Available

Número de parte	UPC	Color	Grosor	Dimensiones	Parte común	UOM
-----------------	-----	-------	--------	-------------	-------------	-----