



www.wearwell.com

ErgoDeck Diamond-Plate Heavy Duty

Group 591

The ultimate ergonomic floor for heavy use. ErgoDeck Diamond-Plate Heavy Duty Solid, offers the industrial look that says stand on me, I can take it. The [LockSafe®](#) Positive Interlocking System design delivers secure connections yet still offers the ability to unlock tiles for repositioning as work centers change to fit production needs. The optional 6" (15 cm) side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck Diamond-Plate Heavy Duty is the best choice in areas with heavy cart and foot traffic. Why? A firmer compound and underside box-spring design provides structural support and impact absorption providing health, safety and productivity [benefits](#). Even in the hardest wet or dry, multi-shift operations.

- Standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Overall thickness 7/8"

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC

Recycled >80%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 0.48% loss
Temperature Range	-17 to 49_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet: COF = .77
Compression Deflection	ASTM D575-91 /15%, Distance: .14
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
591.78x18x18BK-CS10	715411002641	Black	0.875	46 x 46	Y	EA
591.78x18x18CH-CS10	715411698400	Charcoal	0.875	46 x 46	Y	CS-10