



Standard Corrugated Vinyl

Group 381

Our most popular runner, Standard Corrugated Vinyl protects floors, reduces cleaning costs and adds traction where it's needed.

- Protects floors, 3 mm (1/8") thick
- Easy to clean, chemical resistant surface
- Vinyl compound won't curl during use

www.wearwell.com

Wearwell Categories	Runner
Suitable Environment	Dry
Customisation Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	PVC
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	-23 to 49_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .91 / Wet: COF = .65
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
381.18x2x105BK	715411502929	Black	0.125	61 cmx 3200 cm	Y	RL
381.18x2x150BK	715411502806	Black	0.125	61 cmx 4572 cm	Y	RL
381.18x2x75BK	715411429219	Black	0.125	61 cm x 2286 cm	Y	RL
381.18x3x105BK	715411503223	Black	0.125	91 cm x 3200 cm	Y	RL
381.18x3x150BK	715411503100	Black	0.125	91 cm x 4572 cm	Y	RL
381.18x3x75BK	715411429226	Black	0.125	91 cm x 2286 cm	Y	RL
381.18x4x105BK	715411503520	Black	0.125	122 cm x 3200 cm	Y	RL
381.18x4x150BK	715411503407	Black	0.125	122 cm x 4572 cm	Y	RL
381.18x4x75BK	715411429233	Black	0.125	122 cm x 2286 cm	Y	RL