



www.wearwell.com

Ultra-Tred ArmorCote

Group 440

UltraTred ArmorCote has a more durable urethane outer skin than standard blown PVC sponge products. This tough outer skin increases service life, especially in applications where abrasion can cause the mat to fail. UltraTred ArmorCote works longer where other entry-level sponge mats fail.

- Economic comfort for medium traffic areas
- Polyurethane coating for greater abrasion resistance
- Safety rounded edges
- Overall thickness 9 mm (3/8")

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry

Customisation Level C1 - Custom Length

Solid or Drainage Solid

Compound Polyurethane Coating over PVC Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	DOT FMVSS 302- Pass
Taber Abrasion	Not Available
Temperature Range	-20 F to 160 F
Coefficient of Friction	Not Available
Compression Deflection	Not Available
Tear Strength	ASTM D624 - 15 lb/in minimum
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
440.38x2x3BYL	715411240784	Black w/Yellow Borders	0.375	61 cm x 91 cm	N	EA
440.38x2x60BYL	715411240753	Black w/Yellow Borders	0.375	61 cm x 1829 cm	N	RL
440.38x3x12BYL	715411249077	Black w/Yellow Borders	0.375	91 cm x 366	N	EA
440.38x3x5BYL	715411240968	Black w/Yellow Borders	0.375	91 cm x 152 cm	N	EA
440.38x3x60BYL	715411240937	Black w/Yellow Borders	0.375	91 cm x 1829 cm	N	RL
440.38x4x60BYL	715411241057	Black w/Yellow Borders	0.375	122 cm x 1829 cm	N	RL