



www.wearwell.com

Endurable

Group 459

Endurable outlasts lower quality blown sponge products. The technical reason is its “dual layer” construction. The practical result is that a thicker, denser PVC surface withstands abrasion and foot traffic while the softer under layer provides ergonomic relief. Endurable is a great value for the investment.

- Economic relief for medium traffic areas
- Safety beveled edges
- Overall thickness 13 mm (1/2")

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry
Customisation Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	Dual Density PVC Sponge
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Fed Std. 191 / 2% lost @ 1,000 cycles
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677 / Dry: COF = .91
Compression Deflection	ASTM D575 / .23 inches @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
459.12x2x3BK	715411252138	Black	0.5	61 cm x 91 cm	Y	EA
459.12x2x60BK	715411252077	Black	0.5	61 cmx 1829 cm	Y	RL
459.12x3x12BK	715411252312	Black	0.5	91 cm x 366	Y	EA
459.12x3x5BK	715411252374	Black	0.5	91 cm x 152 cm	Y	EA
459.12x3x60BK	715411252251	Black	0.5	91 cm x 1829 cm	Y	RL
459.12x4x60BK	715411252497	Black	0.5	122 cm x 1829 cm	Y	RL