



[www.wearwell.com](http://www.wearwell.com)

## WorkSafe® Light CFR

### Group 478

WorkSafe Light is a Special Teams player that has a unique but hard-to-beat skill set. An invaluable matting solution for cutting fluid environments where sure footing, quick drainage, and fatigue reduction are essential. WorkSafe Light has been doing its job--always well--in some of the toughest, dirtiest, most challenging locations one can imagine. Popular around the world for its versatility and dependability, WorkSafe Light will never let you down!

- Lightweight
- High Performance
- Cutting Fluid Resistant
- Overall thickness 13 mm (1/2")

<b>Wearwell Categories</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Wet, Oily
<b>Customisation Level</b>	Standard Sizes Only
<b>Solid or Drainage</b>	Drainage
<b>Compound</b>	Cutting Fluid Resistant Rubber
<b>Recycled</b>	<10%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Not Available
Temperature Range	-12 to 121_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = > .90 / Wet: COF = .36
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=4.10
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
478.12x3x10GY	715411536603	Gray	0.5	91 cm x 305 cm	Y	EA
478.12x3x20GY	715411536030	Gray	0.5	91 cm x 610 cm	Y	EA
478.12x3x5GY	715411538010	Gray	0.5	91 cm x 152 cm	Y	EA