



www.wearwell.com

Abrasive Coated Kushion Walk Slotted

Group 480-SLT

Abrasive Coated Kushion Walk features our unique GRITSHIELD surface, specifically designed for high COF [Coefficient of Friction] in the slickest locations. With slips and falls being such a dangerous nuisance in today's workplace, Abrasive Coated Kushion Walk offers an effective standing solution in areas requiring high traction.

- Industrial tough and abrasion resistant
- Durable textured surface guards against slipping
- Highly cut resistant. Excellent choice for covering grated walkways
- Also available in solid version
- Overall thickness 9 mm (3/8")

Wearwell Categories	Industrial Runner
Suitable Environment	Wet, Oily, Slippery
Customisation Level	C1 - Custom Length
Solid or Drainage	Drainage
Compound	PVC
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Fed Std. 191 / 1% lost @ 1,000 cycles
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.03 / Wet: COF = .81
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
480.38x2x60SLTBK	715411404216	Black	0.375	61 cmx 1829 cm	Y	RL
480.38x3x60SLTBK	715411404452	Black	0.375	91 cm x 1829 cm	Y	RL