



www.wearwell.com

Vitality Interlocking Tile 91cm x 91cm Modular Configurable Anti-fatigue Matting

Group 502-F

Vitality Flooring features large 91 cm x 91 cm (3'x3') modules--and now new 30 cm x 91 cm (1'x3') modules as well-- that interlock on all 4 sides to customise on-site virtually any flooring configuration. The interlock is incredibly effective--and also hidden--so the ergonomic floor you've created is seamless and stable underfoot. Having the ability to customise in 30 cm (1') increments and finish off with beveled ramps [yellow or black] sets Vitality Flooring apart from all other Polyurethane "wannabees".

- Meets the ASTM G21 standard for anti-microbial properties
- Configure large areas quickly
- Deep Positive Lock keeps seams secure
- 100% Polyurethane with thick outer wear layer
- Customisable in 30 cm (1') increments
- Overall thickness 16mm (5/8")

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Polyurethane

Recycled <10%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	-46 to 121_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .75 / Wet: COF = .28, DIN 51130 - R10
Compression Deflection	ASTM D 395 / 30 minutes 5.67 / 24 hours 1.42
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
502.58x1x3BK	715411004584	Black	5/8"	30 x 91 cm	Y	EA
502.58X3X3BK	715411284306	Black	0.625	91 cm x 91 cm	Y	EA
SF502TR		Black	5/8"			