



www.wearwell.com

ErgoDeck Heavy Duty Open

Group 560

A dependable, ergonomic floor that will withstand heavy use. The patented LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 15 cm (6") wide safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck Heavy Duty is the best choice in areas with heavy cart and foot traffic. Why? The firmer compound lets carts roll over the tiles with ease. Meanwhile, the underside box-spring design provides structural support and impact absorption for health and productivity, even in multi-shift operations.

- U.S. PATENT NO. D502,557; D520,650
- Standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version and with GRITSHIELD for extra traction
- Overall thickness 7/8"
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Learn more about ErgoDeck ergonomic flooring [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Drainage

Compound PVC

Recycled >80%

Warranty Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	-17 to 49_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42, DIN 51130 - R10
Compression Deflection	ASTM D575-91 / 4.84%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
560.78x18x18BK-CS10	715411510412	Black	0.875	46 x 46	Y	CS-10