



www.wearwell.com

ErgoDeck® Heavy Duty Solid with Gritshield®

Group 563

A dependable, ergonomic floor that will withstand heavy use. The patented LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 15 cm (6") wide safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck Heavy Duty is the best choice in areas with heavy cart and foot traffic. Why? The firmer compound lets carts roll over the tiles with ease. Meanwhile, the underside box-spring design provides structural support and impact absorption for health and comfort, even in multi-shift operations. ErgoDeck Heavy-Duty with GRITSHIELD delivers 40% more traction and withstands heavy use and cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Secure footing in slippery applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Learn more about the different versions of ErgoDeck in our blog - [ErgoDeck Ergonomic Interlocking Floor Tiles - Which Version Should I Choose?](#)

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC

Recycled >80%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	-17 to 49_ Celsius
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93, DIN 51130 - R13
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
563.78x18x18BK	715411570911	Black	0.875	46 x 46	Y	EA
563.78x18x18BK-CS10	715411570904	Black	0.875	46 x 46	Y	CS-10

