


www.wearwell.com

ErgoDeck® General Purpose Solid with Gritshield®

Group 567

A high traction, ergonomic floor that will withstand heavy use. The patented LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and re-positioned as work centers change to fit customer needs. The optional 15 cm (6") side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose with GRITSHIELD increases traction by 40% and addresses worker health and safety in areas with primarily foot traffic and light cart traffic.

- Softer compound for greater standing relief in wet or dry applications
- Customise in 8 cm (3") increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version and with GRITSHIELD for extra traction
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC

Recycled >80%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	-17 to 49_ Celsius
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93, DIN 51130 - R13
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
567.78x18x18CH	715411061617	Charcoal	0.875	46 x 46	Y	EA
567.78x18x18CH-CS10	715411060023	Charcoal	0.875	46 x 46	Y	CS-10