



www.wearwell.com

24/Seven® Solid GR - Interlocking Rubber Floor Tiles 3' x 3'

Group 570-GR

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges. [Check out our NEW & IMPROVED 24/SEVEN LockSafe!](#)

◦ Available in 3 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- CFR- Mineral oil-based fluids
- NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Grease Resistant Natural Rubber (GR)

Recycled >50%

Warranty 1 Year

| Property | Test / Result |
|-------------------------|--|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | -12 to 43_ Celsius |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .78 / Wet COF = .68, DIN 51130 - R10 |
| Compression Deflection | Not Available |
| Tear Strength | Not Available |
| ESD Rating | Not Available |
| Dielectric Strength | Not Available |

| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|----------------|--------------|--------|-----------|---------------|------------|-----|
| 570.58x3x3GRBK | 715411414840 | Black | 0.625 | 91 cm x 91 cm | Y | EA |