



www.wearwell.com

24/Seven Open CFR - Interlocking Rubber Floor Tiles 3' x 3'

Group 572-CFR

24/Seven is the family name for Wearwell's high performance, 91 cm x 91 cm (3' x 3'), interconnecting rubber anti-fatigue mats. These resilient modular mats are 16 mm (5/8") thick and tough enough to handle multiple shifts, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas quickly. Or use as single workstations and assembly lines. For extra safety attach optional 8 x 99 cm (3 x 39") yellow safety beveled edges.

◦ Available in 3 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- CFR- Mineral oil-based fluids
- NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Drainage

Compound Cutting Fluid Resistant Rubber (CFR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	-12 to 60_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = .020, DIN 51130 - R10
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
572.58x3x3CFRBK	715411572342	Black	0.625	91 cm x 91 cm	Y	EA