



www.wearwell.com

## 24/Seven® Solid w/ Gritshield® NBR - Interlocking Rubber Floor Tiles 3' x 3'

Group 574-NBR

**WHILE SUPPLIES LAST!**

[Contact us for pricing](#)

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges.

[Check out our NEW & IMPROVED 24/SEVEN LockSafe!](#)

- Available in 2 different rubber compounds based on environmental exposures:

- CFR- Mineral oil-based fluids
  - NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

<b>Wearwell Categories</b>	Anti-Fatigue Flooring
<b>Suitable Environment</b>	Dry, Wet, Oily, Slippery
<b>Customisation Level</b>	C3 - Full Custom (Length, Width, Shape)
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	Nitrile Rubber (NBR)
<b>Recycled</b>	>50%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	-12 to 60_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet COF = 1.10, DIN 51130 - R13
Compression Deflection	ASTM D 575 / Deflection @35 psi, mm= 8.02, inches = .315
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
574.58x3x3NBRBK	715411139309	Black	0.625	91 cm x 91 cm	Y	EA