



[www.wearwell.com](http://www.wearwell.com)

## Autoclavable Mat

### Group 580

Autoclavable Mat is the standing product of choice in sterile environments such as the hospital OR, surgery centers, laboratories, pharmaceutical, and life sciences. The rubber surface domes—flexible and resilient underfoot—provide long-lasting relief for long shifts and extended standing. Featuring a 100% latex-free, non-porous rubber compound, Autoclavable Mat promotes health & wellness for professionals working in sterile applications.

- 100% anti-microbial, USP 797 compliant
- Latex-Free, non-porous rubber compound
- 100% nitrile rubber
- Overall thickness 13 mm (1/2")

**Wearwell Categories** Anti-Fatigue Matting

**Suitable Environment** Dry, Wet, Oily

**Customisation Level** Standard Sizes Only

**Solid or Drainage** Solid

**Compound** Grease Proof Nitrile Rubber

**Recycled** <10%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191/ 1% lost @ 1000g, CS-17 wheel
Temperature Range	Tested at 52 autoclave cycles - 120 degrees C @15 psi for 20 minutes with no deformation
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet: COF = .68
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
580.12x2x3GY	715411011643	Gray	0.5	61 cm x 91 cm	Y	EA