



www.wearwell.com

Static Dissipative Anti-Fatigue

Group 791

Static Dissipative Anti-Fatigue is an ideal ergonomic standing solution for manufacturing, pharmaceutical, and commercial areas where static electricity can pose a problem. What makes this product such a standout is the homogeneous carbon layer, which assures the speedy dissipation of static. Add to that our exclusive Nitricell sponge base, and you've got a star performer that lasts for years while providing unparalleled ergonomic benefits. Note: Each mat includes an attached grounding snap. Mat must be grounded with a ground cord [available from Wearwell and workers must wear a heel grinder [also available] or shoes with conductive soles.

- EOS/ESD S7.1: 1×10^6 to 1×10^{10}
- NFSI Certified
- "Best" sponge base
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness 13 mm (1/2")

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry

Customisation Level C1 - Custom Length

Solid or Drainage Solid

Compound PVC Surface With Nitrile Infused Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191
Temperature Range	-17 to 43_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .62 / Wet: COF = .17
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: RTT= 1×10^6 to 1×10^{10}
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
791.12x2x3GY	715411441747	Gray	0.5	61 cm x 91 cm	Y	EA
791.12x3x5GY	715411442287	Gray	0.5	91 cm x 152 cm	Y	EA
791.12x3x75GY	715411442454	Gray	0.5	91 cm x 2286 cm	N	RL