



www.wearwell.com

24/Seven® LockSafe® Rubber Interlocking Floor Tiles - NBR Diamond Plate

Group 579-NBRDP

New! 24/Seven Locksafe now available with the popular diamond-plate traction surface. Get all the benefits of the 24/Seven LockSafe modular floor tiles plus a diamond-plate surface for even more safety and good looks.

Your anti-fatigue matting program should work for you, not against you. Traditional rubber mats have connections that fail, leaving unsightly trip hazards. Wearwell's 24/SEVEN® LockSafe® includes a Positive Interlock System for a dependable safe, ergonomic floor that only comes apart when you want it to.

The male and female connectors on all sides have a flange that lock together and won't come apart until you want them to! Lift up, roll up and roll away for removal or maintenance. The large 3 foot x 3 foot (91cm x 91cm) tiles make for a quick, easy installation for large areas. **To fit tighter spaces 24/Seven LockSafe can be cut every 12 inches without losing the ability to connect tiles.** Now, with the diamond-plate surface pattern, workers will enjoy even better traction and added safety.

Available in 2 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- NBR- Petroleum-based fluids
- Hidden positive interlocking system
- Choice of solid, domed or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12" (30 cm)

increments

- Overall thickness 5/8" (16 mm)

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	-12 to 60_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = .020, DIN 51130 - R10
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
579.58x3x3NBRBK	715411702954	Black	0.625	91 cm x 91 cm	Y	EA