



www.wearwell.com

24/Seven® LockSafe® Drainage NBR - Interlocking Rubber Floor Tiles 3' x 3'

Group 578-NBR

Performance meets comfort for wet, oily environments. 24/SEVEN LockSafe NBR is ideal for high chemical resistance in high-demand areas. The [Nitrile rubber](#) compound is ideal for harsh environments and the open design allows for optimum [drainage](#).

These large 3'x3' rubber tiles require no tools for assembly making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them.

The Positive Interlock System provides a secure connection in all directions so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

- Available in 3 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- CFR- Mineral oil-based fluids
- NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

| | |
|-----------------------------|---|
| Wearwell Categories | Anti-Fatigue Flooring |
| Suitable Environment | Dry, Wet, Oily, Slippery |
| Customisation Level | C3 - Full Custom (Length, Width, Shape) |
| Solid or Drainage | Drainage |
| Compound | Nitrile Rubber (NBR) |
| Recycled | >50% |
| Warranty | 1 Year |

| Property | Test / Result |
|-------------------------|--|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | -12 to 60_ Celsius |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .90 / Wet COF = 020, DIN 51130 - R10 |
| Compression Deflection | Not Available |
| Tear Strength | Not Available |
| ESD Rating | Not Applicable |
| Dielectric Strength | Not Applicable |

| | | | | | | |
|-----|-----|--------|-----------|------------|------------|-----|
| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|-----|-----|--------|-----------|------------|------------|-----|

| | | | | | | |
|-----------------|--------------|-------|-------|---------------|---|----|
| 578.58x3x3NBRBK | 715411703081 | Black | 0.625 | 91 cm x 91 cm | Y | EA |
|-----------------|--------------|-------|-------|---------------|---|----|