



www.wearwell.com

24/Seven® LockSafe® Interlocking Rubber Floor Tiles - Solid NBR w/ Gritshield®

Group 584-NBR

[Slip prevention](#) and anti-fatigue in one. 24/SEVEN® LockSafe® NBR with GRITSHIELD® is ideal for high chemical resistance in high-demand areas. The solid surface is ideal for foot or [cart traffic](#) in slippery environments. These large 3'x3' rubber tiles interlock and require no tools making installation to any configuration quick and easy. Use optional 24/SEVEN NBR edging and corners when and where you need them.

The Positive Interlock System provides a secure connection in all directions, so you don't have to worry about them coming apart even with heavy foot traffic. Secure connections, lightweight design, and unmatched flexibility allow assembled sections to be lifted up, rolled up, and rolled away for removal or maintenance. Tiles hold together and only come apart when you want them to.

◦ Available in 3 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- CFR- Mineral oil-based fluids
- NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	-12 to 60_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = .020, DIN 51130 - R10
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
584.58x3x3NBRBK	715411702916	Black	0.625	91 cm x 91 cm	Y	EA

