



www.wearwell.com

24/Seven® Open NBR - Interlocking Rubber Floor Tiles 3' x 3'

Group 572-NBR

24/Seven is a collection of high performance, 3'x3' (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8" (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it's needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges. [Check out our NEW & IMPROVED 24/SEVEN LockSafe!](#)

◦ Available in 3 different rubber compounds based on environmental exposures:

- GR- Water or dry debris
- CFR- Mineral oil-based fluids
- NBR- Petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 30 cm (12") increments
- Overall thickness 16 mm (5/8")

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	-12 to 43_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .68, DIN 51130 - R10
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
572.58x3x3NBRBK	715411381616	Black	0.625	91 cm x 91 cm	Y	EA