



www.wearwell.com

UltraSoft Tile-Top AM - Charcoal

Group 419CH

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and chemical resistance in dry areas.

- Features Best Nitricell Sponge for extended performance of anti-fatigue mats
- Wearwell brand Lay-flat design - Built-in trip prevention with beveled safety edges
- Works for workstations and standing height desks
- Available in multiple colors & sizes
- 20% more standing area
- NFSI Certified
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about Tile-Top ergonomic matting [here](#).

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry
Customisation Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	ASTM D395-98 / 20%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMCH	715411033256	Charcoal	0.875	61 cm x 91 cm	Y	EA
419.78x2X60AMCH	715411031689	Charcoal	0.875	61 cm x 1829 cm	Y	RL
419.78x3X10AMCH	715411106578	Charcoal	0.875	91 cm x 305 cm	N	EA
419.78x3X5AMCH	715411032686	Charcoal	0.875	91 cm x 152 cm	Y	EA
419.78x3X60AMCH	715411031757	Charcoal	0.875	91 cm x 1829 cm	Y	RL
419.78x4X60AMCH	715411029181	Charcoal	0.875	122 cm x 1829 cm	Y	RL