



www.wearwell.com

UltraSoft Tile-Top AM - Grey

Group 419GY

Anti-Microbial (AM) top to bottom. The AM Nitrile rubber composite sponge offers maximum comfort and resilience while the AM surface delivers additional abrasion and chemical resistance in dry areas.

- Wearwell brand Lay-flat design - Built-in trip prevention with beveled safety edges
- Mat features 20% more standing area
- Perfect mat for workstations and standing height desks
- Available in multiple colors & sizes
- 7/8" thick for Maximum comfort and ergonomic properties
- NFSI Certified
- Easy cleaning, low maintenance floor covering
- **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

[Learn more about Tile-Top ergonomic matting](#)

[here.](#)

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry
Customisation Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	ASTM D395-98 / 20%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
419.78x2x3AMGY	715411033850	Gray	0.875	61 cm x 91 cm	Y	EA
419.78x2X60AMGY		Gray	0.875	2' x 60'	Y	RL
419.78x3X10AMGY	715411328208	Gray	0.875	91 cm x 305 cm	N	EA
419.78x3X5AMGY	715411029037	Gray	0.875	91 cm x 152 cm	Y	EA
419.78x3X60AMGY	715411032051	Gray	0.875	91 cm x 1829 cm	Y	RL
419.78x4X60AMGY		Gray	0.875	4' x 60'	Y	RL