



www.wearwell.com

Tuf Sponge - Grey

Group 451GY

Wearwell's Tuf Sponge is for use in all dry work areas, an excellent choice for practical and economical comfort. Made from blown PVC sponge, Tuf Sponge reduces floor hardness up to 50% and can easily be custom cut to fit your work areas. 3/8" overall thickness with safety rounded edges.

- Economic comfort for light industrial applications
- Safety rounded edges
- Can easily be cut to size on-site
- Overall thickness 3/8"

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry
Customisation Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	PVC Sponge
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	DOC FF1-70 / Flame Retardant Rating
Taber Abrasion	Fed Std. 191 Modified / 2% lost @ 1,000 cycles
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .94 / Wet: COF = .72
Compression Deflection	ASTM D575 / .205 @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
451.38x2x3GY	715411244089	Gray	0.375	61 cm x 91 cm	N	EA
451.38x2x60GY	715411243990	Gray	0.375	61 cmx 1829 cm	N	RL
451.38x3x12GY	715411244362	Gray	0.375	91 cm x 366	N	EA
451.38x3x5GY	715411244355	Gray	0.375	91 cm x 152 cm	N	EA
451.38x3x60GY	715411244263	Gray	0.375	91 cm x 1829 cm	N	RL
451.38x4x60GY	715411244539	Gray	0.375	122 cm x 1829 cm	N	RL