



www.wearwell.com

## Tuf Sponge - Black with Yellow Borders

### Group 451BYL

Wearwell's Tuf Sponge is for use in all dry work areas, an excellent choice for practical and economical comfort. Made from blown PVC sponge, Tuf Sponge reduces floor hardness up to 50% and can easily be custom cut to fit your work areas. 3/8" overall thickness with safety rounded edges.

- Economic comfort for light industrial applications
- Safety rounded edges
- Can easily be cut to size on-site
- Overall thickness 3/8"

<b>Wearwell Categories</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Dry
<b>Customisation Level</b>	C1 - Custom Length
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	PVC Sponge
<b>Recycled</b>	<10%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	DOC FF1-70 / Flame Retardant Rating
Taber Abrasion	Fed Std. 191 Modified / 2% lost @ 1,000 cycles
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .94 / Wet: COF = .72
Compression Deflection	ASTM D575 / .205 @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
451.38x2x3BYL	715411244034	Black w/Yellow Borders	0.375	61 cm x 91 cm	Y	EA
451.38x2x60BYL	715411243945	Black w/Yellow Borders	0.375	61 cm x 1829 cm	Y	RL
451.38x3x12BYL	715411244348	Black w/Yellow Borders	0.375	91 cm x 366	N	EA
451.38x3x5BYL	715411244317	Black w/Yellow Borders	0.375	91 cm x 152 cm	Y	EA
451.38x3x60BYL	715411244218	Black w/Yellow Borders	0.375	91 cm x 1829 cm	Y	RL
451.38x4x60BYL	715411244485	Black w/Yellow Borders	0.375	122 cm x 1829 cm	Y	RL