



Tile-Top Select - Blue

Group 494BL

Good overall Performance. Flex-Link sponge base is a specially formulated blown-vinyl. More economically priced than the original Tile-Top mats, this Select version also effectively prevents worker fatigue in dry commercial areas. Available in stock sizes, rolls and cut lengths.

- "Better" sponge base
- Available in 1/2" and 7/8" thick

www.wearwell.com

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry

Customisation Level C1 - Custom Length

Solid or Drainage Solid

Compound PVC Surface With PVC Sponge

Recycled <10%

Warranty 3 Years

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .79
Compression Deflection	ASTM D395-98 / 30%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
494.12x2x3BL	715411256044	Blue	0.5	61 cm x 91 cm	Y	EA
494.12x2x60BL		Blue	1/2"	61 cm x 1829 cm	Y	RL
494.12x3x5BL	715411256464	Blue	0.5	91 cm x 152 cm	Y	EA
494.12x3x60BL		Blue	0.5	91 cm x 1829 cm	Y	RL
494.12x4x60BL		Blue	0.5	122 cm x 1829 cm	Y	RL
494.78x2x3BL	715411116171	Blue	0.875	61 cm x 91 cm	Y	EA
494.78x2x60BL		Blue	0.875	61 cm x 1829 cm	Y	RL
494.78x3x5BL	715411118144	Blue	0.875	91 cm x 152 cm	Y	EA
494.78x3x60BL		Blue	0.875	91 cm x 1829 cm	Y	RL
494.78x4x60BL		Blue	0.875	122 cm x 1829 cm	N	RL