



## Tile-Top Select - Charcoal

### Group 494CH

Good overall Performance. Flex-Link sponge base is a specially formulated blown-vinyl. More economically priced than the original Tile-Top mats, this Select version also effectively prevents worker fatigue in dry commercial areas. Available in stock sizes, rolls and cut lengths.

- "Better" sponge base
- Available in 1/2" and 7/8" thick

[www.wearwell.com](http://www.wearwell.com)

<b>Wearwell Categories</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Dry
<b>Customisation Level</b>	C1 - Custom Length
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	PVC Surface With PVC Sponge
<b>Recycled</b>	<10%
<b>Warranty</b>	3 Years

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .79
Compression Deflection	ASTM D395-98 / 30%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
494.12x2x3CH	715411152131	Charcoal	0.5	61 cm x 91 cm	Y	EA
494.12x2x60CH		Charcoal	0.5	61 cm x 1829 cm	Y	RL
494.12x3x5CH	715411152858	Charcoal	0.5	91 cm x 152 cm	Y	EA
494.12x3x60CH		Charcoal	0.5	91 cm x 1829 cm	Y	RL
494.12x4x60CH		Charcoal	0.5	122 cm x 1829 cm	Y	RL
494.78x2x3CH	715411174102	Charcoal	0.875	61 cm x 91 cm	Y	EA
494.78x2x60CH		Charcoal	0.875	61 cm x 1829 cm	Y	RL
494.78x3x5CH	715411176809	Charcoal	0.875	91 cm x 152 cm	Y	EA
494.78x3x60CH		Charcoal	0.875	91 cm x 1829 cm	Y	RL
494.78x4x60CH		Charcoal	0.875	122 cm x 1829 cm	Y	RL