



www.wearwell.com

Double Duty Switchboard Corrugated Mat - Black with Yellow Borders

Group 720BYL

Switchboard matting protects workers from harmful, even deadly shock. This unique non-conductive anti-fatigue mat features a premium Nitricell sponge base, making it first in class for comfort and safety.

- “Best” sponge base
- NFSI (National Floor Safety Institute) Certified
- Surface conforms to ANSI/ASTM D178 01, Type II, Class 2
- Insulates up to 40,000 volts of electricity
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Meant for use in dry, indoor areas
- Overall thickness 5/8”
- **Need a different size?** 1’ incremental lengths are available! [Simply give us a shout out!](#)

Wearwell Categories Non-Conductive Anti-Fatigue Matting

Suitable Environment Dry

Customisation Level C1 - Custom Length

Solid or Drainage Solid

Compound PVC Surface With Nitrile Infused Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	ASTM D178-01: 0.224 mm /s
Taber Abrasion	Fed. Std. 191: 1% lost @ 1,000 cycles
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677: Dry COF .91
Compression Deflection	Not Available
Tear Strength	ASTM D412-98a Die C 1212 psi
ESD Rating	Not Applicable
Dielectric Strength	Surface conforms to ANSI/ASTM D178 01, Type II, Class 2: 30,000 volts. (Recommended Max Usage up to 17,000 volts)

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
720.58x3X5BYL	715411003464	Black w/Yellow Borders	0.625	91 cm x 152 cm	Y	EA
720.58x3X75BYL	715411003341	Black w/Yellow Borders	0.625	91 cm x 2286 cm	Y	RL