



www.wearwell.com

Tile-Top AM with WOW! Finish - Blue

Group 820BL

Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. WOW!, a special finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. WOW! finally solves this decades old problem. Tile-Top AM with WOW! has a tough surface and thick ergonomic build. With Anti-Microbial properties through and through, Tile-Top AM takes your protection to the next level, preventing slips, trips, falls- and contamination.

- WOW! finish prevents mats from sliding on any floor

Premium Anti-Microbial sponge

- Anti-Microbial through and through
- Designed to prevent slips, trips & falls
- Maximized standing area
- Overall thickness 1/2" (12.7mm)

◦ **Need a different size?** 1' incremental lengths are available! [Simply give us a shout out!](#)

Learn more about the ergonomics and benefits of WOW! Finish in our blog - [#STOPSLIDINGMATS](#).

Wearwell Categories Anti-Fatigue Matting

Suitable Environment Dry

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC Surface With Anti-Microbial Nitrile Infused Sponge

Recycled <10%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
820.12x2x3AMBL		Blue	1/2"	2' x 3'	Y	EA
820.12x2x60AMBL		Blue	1/2"	2' x 60'	N	Roll
820.12x3x5AMBL		Blue	1/2"	3' x 5'	Y	EA
820.12x3x60AMBL		Blue	1/2"	3' x 60'	Y	Roll
820.12x4x60AMBL		Blue	1/2"	4' x 60'	N	Roll

