



www.wearwell.com

Tile-Top AM with WOW! Finish - Black

Group 820BK

Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. WOW!, a special finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. WOW! finally solves this decades old problem. Tile-Top AM with WOW! has a tough surface and thick ergonomic build. With Anti-Microbial properties through and through, Tile-Top AM takes your protection to the next level, preventing slips, trips, falls- and contamination.

- WOW! finish prevents mats from sliding on any floor
- Premium extra thick Anti-Microbial sponge
- Anti-Microbial through and through
- Designed to prevent slips, trips & falls
- Maximized standing area
- Overall thickness 1/2" (12.7mm)

Wearwell Categories	Anti-Fatigue Matting
Suitable Environment	Dry
Customisation Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC Surface With Anti-Microbial Nitrile Infused Sponge
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
820.12x2x3AMBK		Black	1/2"	2' x 3'	Y	EA
820.12x2x60AMBK		Black	1/2"	2' x 60'	N	Roll
820.12x3x5AMBK		Black	1/2"	3' x 5'	Y	EA
820.12x3x60AMBK		Black	1/2"	3' x 60'	Y	Roll
820.12x4x60AMBK		Black	1/2"	4' x 60'	N	Roll