

24/Seven LockSafe Female Edging, Grease Resistant Black



Group 578-FGRBK

24/Seven LockSafe female edging is Grease Resistant and securely interlocks with 24/Seven LockSafe modular tiles. Black edging creates a seamless and smooth transition for foot traffic.

Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

www.wearwell.com

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound

Recycled >50%

Warranty Lifetime

| Property | Test / Result |
|-------------------------|---|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | 10 to 140 F |
| Coefficient of Friction | ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94 |
| Compression Deflection | Not Available |
| Tear Strength | Not Available |
| ESD Rating | Not Available |
| Dielectric Strength | Not Available |

| | | | | | | |
|-----|-----|--------|-----------|------------|------------|-----|
| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|-----|-----|--------|-----------|------------|------------|-----|