



www.wearwell.com

24/Seven GR (Grease Resistant) Male Edging - Black

Group 572-MGRBK

24/Seven GR (Grease Resistant) male edging securely interlocks with 24/Seven GR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The GR rubber compound is designed for areas with water or dry debris.

- Grease Resistant (GR) rubber
- Ideal for areas with water or dry debris
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Grease Resistant Natural Rubber (GR)

Recycled >50%

Warranty 1 Year

| Property | Test / Result |
|-------------------------|---|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | 10 to 140 F |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .90 / Wet COF = 020 |
| Compression Deflection | Not Available |
| Tear Strength | Not Available |
| ESD Rating | Not Available |
| Dielectric Strength | Not Available |

| | | | | | | |
|-----|-----|--------|-----------|------------|------------|-----|
| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|-----|-----|--------|-----------|------------|------------|-----|