



www.wearwell.com

## 24/Seven CFR Male Edging - Black

### Group 572-MCFRBK

24/Seven CFR (Cutting Fluid Resistant) male edging securely interlocks with 24/Seven CFR rubber floor tiles. Black edging creates a seamless and smooth transition for foot traffic.

The CFR rubber compound is engineered to resist mineral oil-based fluids.

- Cutting Fluid Resistant (CFR) rubber
- Ideal for areas with mineral oil-based fluids
- 3" wide
- Overall thickness 5/8"
- Female edging available
- Available in black and yellow

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry, Wet, Oily, Slippery

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** Cutting Fluid Resistant Rubber (CFR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss Temperature Range
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = 020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----