

24/Seven LockSafe Male Edging, Grease Resistant Yellow



Group 578-MGRYL

24/Seven LockSafe female edging is Grease Resistant and securely interlocks with 24/Seven LockSafe modular tiles. Yellow edging acts as a visual cue and provides a smooth transition for foot traffic.

Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

- Grease Resistant Natural Rubber (GR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and Female Edging available
- Also available in black

www.wearwell.com

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Grease Resistant Natural Rubber (GR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----