



www.wearwell.com

24/Seven LockSafe Corner, Grease Resistant Yellow- Case of 4

Group 578-CGRYL

24/Seven LockSafe corners offer a secure connection with ramps and tiles. These separate corners alleviate the time, costs, and waste associated with traditional modular rubber edging that requires cutting. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or areas where the primary liquid is water.

- For use in dry areas or areas with water
- Grease Resistant Natural Rubber (GR)
- Case of 4
- 3" wide
- Overall thickness 5/8"
- Male and female edging available
- Available in black and yellow

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Grease Resistant Natural Rubber (GR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----