



www.wearwell.com

24/Seven LockSafe Nitrile Rubber (NBR) - Female Edging, Black

Group 578-FNBRBK

24/Seven LockSafe Nitrile Rubber (NBR) female edging securely interlocks with 24/Seven LockSafe NBR modular tiles. NBR is suitable for more demanding areas that require optimum chemical resistance. Black edging creates a seamless and smooth transition for foot traffic.

- Nitrile Rubber (NBR)
- Ideal for dry areas or areas with water
- 3" wide
- Overall thickness 5/8"
- Corners and male edging available
- Available in black and yellow

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry, Wet, Oily, Slippery

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Nitrile Rubber (NBR)

Recycled >50%

Warranty 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----